

PN	Core	Cordic	HCL	FFT	PFM	DCE	GPT	Memory		Signal Chain				Control device							PBUS	Interface								GPIO	Package	Operating Temperature Range(Tj)	Package qty		
								SRAM	FLASH	ADC		PGA	DAC	HRPWM /PWM	CAP	QEP	QOUT	CPM	SDF M	TA-IF/BIS-IF/EDAT-IF		ESC	PHY	USB	EMAC	UART	QSPI	SPI	PC					CAN	
M76P00																																			
M76P08SGKS	2x(RISC-V 552MHz +FPU+DSP)	x1	x2	Y	Y	Y	x4	1MB	2MB	14bit 2Msps x2/24CH		x4	N	24CH/24CH	x6	x10	x2	x2	x4	x2/x2/x2		Y	Y	N	x1	x1	x9	x3	x5	x4	CAN x1 CAN-FD x2	150	BGA196 12x12mm,0.8mm	-40~125°C	盘168 包1680
M76P06SPHS	2x(RISC-V 552MHz +FPU+DSP)	x1	x2	Y	Y	Y	x4	1MB	2MB	14bit 2Msps x2/16CH		x4	N	24CH/24CH	x6	x10	x2	x2	x4	x2/x2/x2		Y	Y	N	x1	x1	x9	x2	x4	x4	CAN x1 CAN-FD x2	122	eLQFP144 20x20mm,0.5mm	-40~125°C	盘60 包600
M76P06SGHS	2x(RISC-V 552MHz +FPU+DSP)	x1	x2	Y	Y	Y	x4	1MB	2MB	14bit 2Msps x2/16CH		x4	N	24CH/24CH	x6	x10	x2	x2	x4	x2/x2/x2		Y	Y	N	x1	x1	x9	x2	x4	x4	CAN x1 CAN-FD x2	118	BGA144 10x10mm,0.8mm	-40~125°C	盘240 包2400
M73P00																																			
M73P06SPHS	1x(RISC-V 552MHz +FPU+DSP)	x1	x1	Y	Y	Y	x4	512KB	1MB	14bit 2Msps x2/16CH		x4	N	24CH/24CH	x6	x10	x2	x2	x4	x2/x2/x2		Y	Y	N	x1	x1	x9	x2	x4	x4	CAN x1 CAN-FD x2	122	eLQFP144 20x20mm,0.5mm	-40~125°C	盘60 包600
M73P06SGHS	1x(RISC-V 552MHz +FPU+DSP)	x1	x1	Y	Y	Y	x4	512KB	1MB	14bit 2Msps x2/16CH		x4	N	24CH/24CH	x6	x10	x2	x2	x4	x2/x2/x2		Y	Y	N	x1	x1	x9	x2	x4	x4	CAN x1 CAN-FD x2	118	BGA144 10x10mm,0.8mm	-40~125°C	盘240 包2400